



243 Winchester

with **Boron Nitride Coating**
90-grain DeepCurl® SP

0.243"	DeepCurl SP
Weight, grains	90
Case	Federal®
Primer	CCI 200, 250*
COAL	2.650"
Speer Part No.	1214

Propellant	START CHARGE		MAXIMUM CHARGE	
	Weight, grs	Muzzle Velocity, ft/sec	Weight, grs	Muzzle Velocity, ft/sec
RE 17	37.0	2795	41.0	3,087
Win 760*	37.0	2,786	41.0	3,044
IMR 4350	38.0	2,765	42.0	3,042
IMR 4831	38.0	2,759	42.0	3,033
Varget	32.0	2,676	36.0	2,918
2000 MR*	33.0	2,617	37.0	2,887

WARNING: DO NOT USE BORON NITRIDE COATED BULLET DATA FOR UNCOATED BULLETS.

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current Speer® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum Loads should be used with CAUTION • C = Compressed Load • * Magnum Primer used with this powder.*