



260 Remington

with **Boron Nitride Coating**
140-grain DeepCurl® SP

0.264"	DeepCurl SP
Weight, grains	140
Case	Federal®
Primer	Fed 210, 215*
COAL	2.750"
Speer Part No.	1436

Propellant	START CHARGE		MAXIMUM CHARGE	
	Weight, grs	Muzzle Velocity, ft/sec	Weight, grs	Muzzle Velocity, ft/sec
RE 19	40.3	2,475	44.3	2,688
4000-MR*	39.5	2,443	43.5	2,685
RE 22	40.5	2,493	44.5	2,684
H4831SC	38.8	2,430	42.8	2,617
IMR4350	36.0	2,365	40.0	2,589

WARNING: DO NOT USE BORON NITRIDE COATED BULLET DATA FOR UNCOATED BULLETS.

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current Speer® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum Loads should be used with CAUTION • C = Compressed Load • * Magnum Primer used with this powder.*